

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: SDS Number: Product Code: Revision Date: Version: Product Type:	Paintable Cube IMS 07-290-01 113133 11/18/2022 2 Mold Release
Supplier Details:	IMS Company 10373 Stafford Rd. Chagrin Falls, OH 44023-5296
Phone:	1-440-543-1615
Emergency:	Chemtel 1-800-255-3924

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

# 2 HAZARDS IDENTIFICATION

#### **Classification of the Substance or Mixture**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS): No GHS Classifications Indicated

#### **GHS Label Elements, Including Precautionary Statements**

#### GHS Signal Word: NONE

#### **GHS Hazard Pictograms:**

No GHS pictograms indicated for this product

#### **GHS Hazard Statements:**

No GHS hazards statements indicated

#### **GHS Precautionary Statements:**

No GHS precautionary statements indicated

## Hazards not Otherwise Classified (HNOC) or not Covered by GHS

#### **Emergency overview:**

**Potential health effects**: This material is not considered hazardous by the OSHA Hazard communication Standard, OSHA 29 CFR 1910.1200

3	COMPOSITION/INFO	RMATION	I OF INGREDIENTS	
	CAS#	Chemic: %	al Ingredients: Chemical Name:	
	8042-47-5	100%	White mineral oil, petroleum	
SDS Number: IMS 07-290-01			Page: 1/6	Revision Date: 11/18/2022

4	FIRST AID MEASURES
Inhalation:	Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.
Skin Contact:	Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Eye Contact:	Flush with warm water for 15 minutes. Seek medical attention.
Ingestion:	Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5	FIRE FIGHTING MEASURES
---	------------------------

Suitable extinguishing media: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire

Special hazards arising from the substance or mixture / Conditions of flammability: Flammable liquid and vapor. Product may ignite when exposed to heat, sparks and direct flame. Vapours are heavier than air and may spread along floors. Product may float, and be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Hazardous combustion products: Carbon oxides; Other unidentified organic compounds

Special protective equipment and precautions for firefighters:

#### Protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures:

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire-fighting to enter drains or water courses. Dike for water control.

#### 6

7

## ACCIDENTAL RELEASE MEASURES

#### **Spill or Leak Instructions**

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## HANDLING AND STORAGE

Handling Precautions:

Handling: FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

Storage Requirements:	Precautions for safe handling: Persons with recurrent skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools with this material. Take precautionary measures against static discharges. Always open containers slowly to allow any excess pressure to vent. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Empty containers may contain residues from the product. Treat empty containers. Oil soaked rags may spontaneously combust; place in appropriate disposal container.
	Incompatible materials: Strong oxidizing agents; Strong acids
8 EXP	OSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	Ventilation and engineering measures: Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.
Personal Protective Equipment:	Respiratory protection: If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection Specialists.
	Skin protection: Wear protective gloves. Wear as appropriate: Nitrile rubber; polyvinyl alcohol; Viton; Barrier; Responder. Unsuitable material Butyl rubber; Natural Rubber; Neoprene gloves; Polyvinylchloride. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
	Eye / face protection: Wear eye/face protection. Wear as appropriate: Tightly fitting safety
	goggles; Safety glasses with side shields. Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
	General hygiene considerations: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing must not be allowed out of the workplace.
	Other Suggested Equipment: Eye wash station and emergency showers should be available. Spill containment equipment should be available.
	Discretion Advised: Chemical Solvents Inc. takes no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.
White mineral oil, petroleum cas	#:(8042-47-5) [100%]
OSHA (PEL) Oil Mist 5mg/M3	

OSHA (PEL) Oil Mist 5mg/M3 ACGIH (TLV) Oil Mist 5mg/M3

9	PHYSICAL AND CHEMICAL PROPERTIES			
Appearance:	Clear Liquid			
Physical State:	Liquid	Odor:	Mild Hydrocarbon	
Viscosity:	Kinematic (40°C (104°F)) .412 cm2/s (41.2 <b>Solubility:</b> Insoluble in water cSt)			
Boiling Point:	NA	Freezing/Melting Pt.:	NA	
Flammability:	NA	Flash Point:	227°C (440°F)	
Partition Coefficient:	>4	Vapor Density:	NA	
Vapor Pressure:	<0.011 kPa (0.08 m Hg room temp.)	Auto-Ignition Temp:	355°C (671°F)	
pH:	NA	UFL/LFL:	NA	
Evap. Rate:	NA			
Decomp Temp:	NA			
10	STABILITY AND REACTIVITY			

Chemical Stability:	Stable
Conditions to Avoid:	Heat, spark, and open flame.
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Hazardous Polymerization:

Will not occur.

11

TOXICOLOGICAL INFORMATION

White mineral oil, petroleum cas#:(8042-47-5) [100%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50 Dermal LD50 Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA

classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Aspiration may lead to:, lipid pneumonia, Effects due to ingestion may include:, laxative effect, Gastrointestinal disturbance, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: PY8047000

# 12 ECOLOGICAL INFORMATION

White mineral oil, petroleum cas#:(8042-47-5) [100%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: Mobility in soil:

PBT and vPvB assessment: no data available

Other adverse effects: no data available

## DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

#### 14

13

### TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101 DOT description: Non-regulated by D.O.T.

## 15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[100%] White mineral oil, petroleum (8042-47-5) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

#### Regulatory Code Legend

TSCA = Toxic Substances Control Act

## 16 OTHER INFORMATION

**NFPA:** Health = 0, Fire = 1, Reactivity = 0, Specific Hazard = n/a



#### Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/18/2022