

**Section 1 – MANUFACTURER INFORMATION**

<b>Manufacturer</b>	IMS Company	Emergency Phone	800-424-9300
	10373 Stafford Road	Prepared by	Product Safety Advisor
	Chagrin Falls, OH 44023-5296	Prepared/Revised	February 18, 2005
	WEB <a href="http://imscompany.com">imscompany.com</a>	E-mail	<a href="mailto:sales@imscompany.com">sales@imscompany.com</a>

**Item # & Product Name:** #131410 Paintable A4 Mold Release with DryFilm with no Ozone-Depleting Substances. Replaces Item #113747 Paintable Mold Release with DryFilm.

**Product Use:** To help plastic parts release from a metal mold in processes such as injection molding.

**Hazardous Material Information System**

<b>Health</b> ..... 1	<b>Flammability</b> ..... 4	<b>Reactivity</b> ..... 1	<b>Protection</b> ..... X
0 Normal use Material	0 Will Not Burn	0 Stable	<b>X = Consult the MSDS and your supervisor for your special workplace need</b>
<b>1 Slight Hazard (temporary)</b>	1 Possible to Burn	<b>1 Unstable if Heated</b>	
2 Health Affected (lengthy)	2 Burns if Heated	2 Violent Chemical Change	
3 Extreme Danger	3 Easily Burns	3 Shock and Heat Sensitive	
4 Severe or Fatal	<b>4 Very Easily Burns</b>	4 May Explode	

NOTE The HMIS may not be enough hazard information for this chemical in all workplaces. The HMIS system requires employee training about the system and about information in this MSDS.

**Section 2 – INGREDIENTS INFORMATION**

Chemical/Common Name	CAS-Number	%	OSHA PEL ppm	OSHA STEL ppm	ACGIH TLV ppm	ACGIH STEL ppm	OTHER ppm
1,1-Difluoroethane (HFC-152a)	75-37-6	35 to 55	NE	NE	NE	NE	1000 <sup>(1)</sup>
Dimethyl Ether	115-10-6	25 to 45	NE	NE	NE	NE	1000 <sup>(1)</sup>
Isohexane <sup>(5)</sup>	107-83-5	25 to 45	NE	NE	500 <sup>(2)</sup>	NE	
Isopropanol	67-63-0	0.1 to 10	400	NE	400	500	2000 <sup>(3)</sup>
Fluorocarbon Telomer Mix	Mixture	0.1 to 10	NE	NE	NE	NE	<sup>(4)</sup> 10 mg/m <sup>3</sup>

<sup>(1)</sup> AIHA WEEL and manufacturer suggested Allowable Exposure Limit (AEL)

<sup>(2)</sup> For hexane isomers

<sup>(3)</sup> NIOSH IDLS

<sup>(4)</sup> AEL 10 mg/m<sup>3</sup>; Respirable fraction 5 mg/m<sup>3</sup>

<sup>(5)</sup> This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**Section 3 – HAZARDS IDENTIFICATION**

Extremely flammable aerosol. Flammable gases are heavier than air and will collect in closed areas. Acute and chronic inhalation hazard. Pressurized containers. Causes slippery floors, which can cause slips and falls.

**Emergency Overview:** Gray to white aerosol, leaving a white powder after evaporation. Toxic fumes released in fire situations. Harmful if inhaled. Can cause death if too much is breathed.

**HEALTH EFFECTS** - Acute and Chronic

**Inhalation:** HARMFUL IF INHALED. Central Nervous System (CNS) depression with anaesthetic effects such as dizziness, headache, confusion, incoordination, and loss of consciousness. Higher exposures to vapors may cause temporary alteration of the heart's electrical activity, with irregular pulse, palpitations, or inadequate circulation; or



554°F (290°C) could cause lung irritation and pulmonary edema, which require medical treatment.

### Section 6 – ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Ventilate area to reduce concentration of the components below their exposure limits. Use protective equipment consistent with the situation. Pick up the spill; store in closed containers for proper disposal. Remove residue to prevent a slippery condition developing.

### Section 7 – HANDLING AND STORAGE

**Precautions to be Taken in Handling and Storage:** Store all industrial chemicals away from food and beverages. Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burn.

**Maintenance Precautions:** Do not remove or deface label.

**Other Precautions:** The inhalation of smoke or fumes of burning tetrafluoroethylene telomer – including those produced from contaminated cigarettes or tobacco – could cause Polymer Fume Fever, a flu-like condition which occurs several hours after exposure and subsides within 24 hours, even in the absence of treatment. Repeat episodes of Polymer Fume Fever might cause lung damage. Flammable vapors are heavier than air and will collect in low areas. Read and follow directions and cautions on the container label, and any accompanying literature. Product can cause slippery surfaces. Clean up spills promptly. Monitor floors for accumulation in overspray area; clean as needed.

### Section 8 – EXPOSURE CONTROLS – PERSONAL PROTECTION

**General:** If clothing is likely to be contaminated, wear polymer-coated apron or other body covering.

**Ventilation:** Local exhaust, or mechanical or special ventilation to maintain exposure limits.

**Respiratory Protection:** Generally not required if sufficient ventilation is provided. If the exposure limits of the product or any of its components are exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier).

**Protective Gloves:** If prolonged or repeated contact is likely, wear solvent-resistant gloves.

**Other Protective Equipment:** If contact with the spray is likely, wear eye protection. Monogoggles or safety glasses with side shields and a face shield will provide protection in most situations. Do not wear contact lenses.

**Other Engineering Controls:** To determine exposure levels, monitoring should be performed. Eyewash station should be available. Overspray is slippery and is difficult to fully remove from floors. Avoid overspray.

**Work Practices:** Do not use in confined or closed space. Ventilation should maintain the concentration of the product and its components below their exposure limits. We consider it good practice to limit exposure less than 10 mg/m<sup>3</sup> TWA total, 5 mg/m<sup>3</sup> respirable fraction.

**Hygienic Practices:** Avoid contact with skin and avoid breathing vapors. Do not eat, drink, or smoke in work area. Wash hands before eating, drinking, or using restroom after using this or any chemical product.

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity (Water = 1) ... < 1	Vapor Pressure (PSIG) ..... 55 ± 10	Vapor Density (Air = 1).... >1
Evaporation Rate (Ether)..... Faster	Solubility in Water ..... Slight	% Volatile ..... >80%
VOC by Volume..... 64%	VOC by Weight ..... 53%	

**Appearance and Odor Information:** White powdery mist with slight ethereal odor as dispensed from the aerosol package.

**Section 10 – STABILITY AND REACTIVITY**

**Incompatibility (Materials to Avoid):** Strong oxidizers, strong caustics, reactive metals such as sodium, potassium, zinc, magnesium, aluminum, alkaline earth metals, ozone, fluorine, chromic anhydride, and beryllium.

**Will Hazardous Polymerization Occur?** No      **Conditions to Avoid for Polymerization:** N/A

**Is the Product Stable?** Yes      **Conditions to Avoid for Stability:** Avoid heat sufficient to burst container (see special fire fighting procedure above) and spraying into flame or onto red hot surfaces, which may cause decomposition.

**Section 11 – TOXICOLOGICAL INFORMATION**

COMPONENT	CARCINOGENICITY			ORAL	INHALATION
	IARC	NTP	ACGIH	TOXICITY	TOXICITY
1,1-Difluoroethane(HFC-152a)	no	no	no	ALD >1500 mg/kg (rat)	ALC 383,000 ppm (4hr/rat)
Dimethyl Ether	no	no	no	NA	164,000 ppm (4hr/rat)
Isohexane	no	no	no	not available	not available
Isopropanol	no	no	no	LD <sub>50</sub> 5045 mg/kg (rat)	LClo 16,000 ppm (4hr/rat)
Fluorocarbon Release Agent:	not available				

**Section 12 – ECOLOGICAL INFORMATION**

Not an ozone-depleting substance.

**Section 13 – DISPOSAL CONSIDERATIONS**

Consult Federal, State and Local regulations. Do not puncture or burn containers. Give empty, leaking, or full containers to a disposal service equipped to handle and dispose of aerosol (pressurized) containers.

**Section 14 – TRANSPORT INFORMATION**

<b>Ground (US DOT)</b>	Consumer Commodity, Class ORM-D, ERG 126;	<b>OR</b>	Aerosols (Limited Quantity), Class 2.1, ERG 126
<b>Air (IATA)</b>	Consumer Commodity, Class 9, UN/ID No. ID 8000, Packing 1900, Authorization: Limited Quantity		

**Section 15 – REGULATORY INFORMATION**

CFC, Class 1, Class 2 .....no      FDA ..... no      USDA H-1, -2 ..... not determined

COMPONENT	CAS#	SARA 313	California PROP 65
none		none	yes

**ADDITIONAL COMMENTS**

**CAUTION Intentional misuse of this chemical product, as with any industrial chemical, in contact with the body can be harmful or fatal. This includes such things as deliberately breathing, placing in mouth, swallowing, placing on skin, or any other body contact, or repeated, or continuous contact.**

IMS provides this information in good faith, but makes no representation as to its comprehensiveness or its accuracy. This document is offered as a guide to a trained person, for appropriate precautionary handling. Persons using the product and receiving the information must exercise independent judgment in determining the appropriateness of the use and the safety information for their particular purpose. IMS MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THIS INFORMATION OR TO THE PRODUCT. ACCORDINGLY, IMS WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE ON THIS INFORMATION.