

**Section 1 – MANUFACTURER INFORMATION**

<b>Manufacturer</b>	IMS Company	Emergency Phone	800-424-9300
	10373 Stafford Road	Prepared by	Product Safety Advisor
	Chagrin Falls, OH 44023-5296	Prepared/Revised	August 5, 2008
	WEB: <a href="http://www.imscompany.com">http://www.imscompany.com</a>	E-mail	<a href="mailto:sales@imscompany.com">sales@imscompany.com</a>

**Products:**Item # 142877 *Night Coat* Rust Preventive & Acid Neutralizer Spray**Product Use:** To preserve finish on tool steels and other critical metal parts**Hazardous Material Information System**

<b>Health</b> ..... 1	<b>Flammability</b> ..... 4	<b>Reactivity</b> ..... 0	<b>Protection</b> ..... X
* Chronic (Accumulates)			
0 Normal use Material	0 Will Not Burn	<b>0 Stable</b>	<b>X = Consult the</b>
<b>1 Slight Hazard (temporary)</b>	1 Possible to Burn	1 Unstable if Heated	<b>MSDS and</b>
2 Health Affected (lengthy)	2 Burns if Heated	2 Violent Chemical Change	<b>your supervisor</b>
3 Extreme Danger	3 Easily Burns	3 Shock and Heat Sensitive	<b>for your special</b>
4 Severe or Fatal	<b>4 Very Easily Burns</b>	4 May Explode	<b>workplace need</b>

NOTE The HMIS may not be enough hazard information for this chemical in all workplaces. The HMIS system requires employee training about the system and about information in this MSDS.

**Section 2 – INGREDIENTS INFORMATION**

<b>Chemical/Common Name</b>	<b>CAS-Number</b>	<b>%</b>
Liquefied Petroleum Gas	68476-86-8	10 to 25
Aliphatic Petroleum Distillate	64742-88-7	60 to 80
Petroleum Lube Oil	64742-65-10	10 to 20
Zinc Dinonylnaphthalenesulfonate	28016-00-4	<1
Calcium Dinonylnaphthalenesulfonate	57855-77-3	<2
Ethylene Glycol Monobutyl Ether	111-76-2	<3
Hexylene Glycol <sup>(1)</sup>	107-41-5	<1

**Section 3 – HAZARDS IDENTIFICATION****CAUTION! CONTENTS UNDER PRESURE****DANGER: EXTREMELY FLAMMABLE****POTENTIAL HEALTH EFFECTS****Routes of exposure:** Skin, eyes, inhalation, ingestion.**Eye Contact:** May cause immediate or delayed irritation. Irritation may show up as redness and/or swelling. May cause corneal damage.**Skin Contact:** Repeated or prolonged contact with skin may produce redness, irritation and/or dryness. May cause or aggravate dermatitis or other existing skin condition.**Inhalation:** Inhalation of vapors or spray mist may cause headaches, and/or nose and throat irritation.**Ingestion:** Ingestion may cause irritation to the mouth, esophagus, and/or stomach.**Signs or Overexposure:** Irritation of eyes, nose, throat, digestive tract.**Target Organs:** Over exposure to this material ( or its components) has been suggested as a cause of the following effects in laboratory animals, and may aggravate pre-existing disorders of these organs in humans: Blood abnormalities, liver abnormalities, anemia, spleen damage, testis damage, kidney damage, lung damage. This product has been shown to cause harm to the fetus in laboratory animals. The relevance to humans is uncertain.

#### 4. First Aid Measures

**Eye Contact:** Flush with warm water for 15 minutes. Seek medical attention.

**Skin Contact:** Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

**Inhalation:** Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

**Ingestion:** Immediately give the person two large glasses of water. Do not induce vomiting. Get medical attention immediately.

DO NOT GIVE AN UNCONCIOUS OR CONVULSING PERSON ANYTHING BY MOUTH!

#### 5. Fire Fighting Measures

**Flash Point:** Flash point of propellant <0° F.

**Flammable limits in air, % by volume:** Upper: No Information Lower: No Information

**Extinguishing Media:** Dry chemical, carbon dioxide, halon or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

**Unusual Fire & Explosion Hazards:** This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

**Special Fire Fighting Procedures:** At elevated temperatures (over 130° F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

#### 6. Accidental Release Measures

**Spill or Leak Instructions:** Avoid breathing vapors. Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind. Keep out of low areas where vapors could accumulate. Ventilate to reduce concentration of components below their exposure limits. Use protective equipment consistent with the situation. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

Pick up spilled liquid on absorbent material. If large release occurs indoors, turn off HVAC system to prevent vapors from contaminating entire building. Petroleum lubricants are likely to be deposited on floors, making them slippery. Immediately scatter sand or similar anti-slip material to prevent slip and fall injuries. Thoroughly clean floors to remove residual lubricants before returning them to service.

Place leaking containers in well-ventilated area.

If required, notify state and local authorities.

#### 7. Handling and Storage

**Handling:** Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent.

Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

**Storage:** Store in a cool, dry area, away from heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

## 8. Exposure Controls / Personal Protection

**Protective Equipment:** Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

**Engineering Controls:** General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

**Respiratory Protection:** Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

**Other Suggested Equipment:** Eye wash station and emergency showers should be available. Spill containment equipment should be available.

**Discretion Advised:** IMS takes no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

### Exposure guidelines:

Chemical/Common Name	CAS-Number	OSHA	ACGIH
Liquefied Petroleum Gas	68476-86-8	1000 PEL	1000 TLV
Aliphatic Petroleum Distillate	64742-88-7	100 VPEL	100 TLV
Petroleum Lube Oil	64742-65-10	5 mg/m <sup>3</sup> <sup>(1)</sup>	5 mg/m <sup>3</sup> <sup>(1)</sup>
Zinc Dinonylnaphthalenesulfonate	28016-00-4	NE	NE
Calcium Dinonylnaphthalenesulfonate	57855-77-3	NE	NE
Ethylene Glycol Monobutyl Ether	111-76-2	25 ppm (skin)	25 ppm (skin)
Hexylene Glycol <sup>(2)</sup>	107-41-5	25 ppm STEL	25 ppm STEL

<sup>(1)</sup> Exposure limit is general limit for oil mist.

<sup>(2)</sup> Exposure limit is for inhalation. Because hexylene glycol does not vaporize readily, likely exposure is limited to direct inhalation of the spray.

## 9. Physical and Chemical Properties

<b>Boiling Point:</b>	NA	<b>Specific Gravity:</b>	<1
<b>Vapor Density (Air = 1):</b>	>1	<b>Water Solubility:</b>	Negligible
<b>Evaporation Rate (Ether = 1):</b>	Slower		
<b>Odor/Appearance:</b> Clear amber mist as dispensed from aerosol can.			

## 10. Stability and Reactivity

**Stability:** Stable

**Conditions to Avoid:** Heat, sparks and open flame

**Incompatibility:** Strong oxidizing agents

**Hazardous Decomposition:** Combustion will produce carbon monoxide, carbon dioxide and nitrogen-oxygen compounds.

**Hazardous Polymerization:** Will not occur

## 11. Toxicological Information

**Component Toxicological Information:** No Data.

## 12. Ecological Information

N/A

### 13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate.

State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

### 14. Transport Information

#### Ground (US DOT)

Consumer Commodity  
Class ORM-D, ERG 126

or

Aerosols (limited quantity),  
Class 2.1, ERG 126

#### AIR (IATA)

Aerosols (limited quantity),  
Class 2.1, ERG 126, UN No. 1950

#### Vessel

Aerosols (limited quantity),  
Class 2.1, UN No. 1950

### 15. Regulatory Information

#### ENVIRONMENTAL REGULATIONS

##### SARA 302/304:

None

##### SARA 311/312:

Immediate ( x ) Delayed ( ) Fire ( x ) Reactive ( ) Sudden Release of Pressure ( x )

#### Section 313

This product contains:

Zinc compounds 28016-00-4 < 1%

Ethylene glycol Monobutyl Ether 111-76-2 < 3%

**All the chemicals used in this product are TSCA listed.**

Check with your local regulators to be sure all local regulations are met.

### 16. Other Information

**Hazard ratings:** This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

**NFPA:** Level 3 Aerosol

**HMIS:** Health: 2 Flammability: 4 Reactivity: 0

Where: 4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = INSIGNIFICANT

**Note:** For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. IMS Company makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an MSDS does not indicate that the possessor of the MSDS was a purchaser or user of the subject product.