



Model 6010 Temperature Indicator

Provides good visible indication, alarm capability and security

This unit has fast identification of alarms via separate LED indicators. Other options include a retransmission output, a 24 volt AC/DC input power supply, plus a remote input for a security lock.

Configuration can be easily setup through the front panel, plus, unauthorized user can be locked out of changing the alarm values and configuration parameters via a simple security code or by a remote.

- Large, red 4-digit LED display
- 3 alarms: latching, relay and multiple alarm options
- Plug and Play technology allows for field upgrades
- Retransmission output
- Security via password protection and remote lock option



Options:

- 20-50VAC, 22-65VDC low voltage option
- RS485 serial communications protocols
- Remote reset

Specifications and Prices

Temperature Range: 32° F to 842° F	Accuracy: ±.25% of span ±1 LSD (least significant digit; typically 1° F)	
Control Output: 1 SPST (2A) relay	Power Input: 90 to 264V AC 50/60Hz	
Item #	Description	Price
128292	Model 6010+ Temperature Indicator (1/16 DIN)	\$227.65

Adaptor Plates

Simplify retrofitting of existing control panels

- 272P to 1/4 DIN
- 1/4 DIN to 1/8 DIN
- 1/4 DIN to 1/16 DIN



Specifications and Prices

Color: grey			
Material: 16 gauge steel			
Dimensions:	Item #	Cutout Dimensions	Panel Dimensions
	119510	92 mm x 92 mm	190 mm x 178 mm
	119508	92 mm x 45 mm	114 mm x 142 mm
	119503	45 mm x 45 mm	142 mm x 114 mm
Item #	Description	Prices	
119510	272P to 1/4 DIN	\$10.00	
119508	1/4 DIN to 1/8 DIN	15.75	
119503	1/4 DIN to 1/16 DIN	15.80	
<i>Ask about other sizes</i>			



www.imscompany.com | phone order toll-free (USA & Canada) **1.800.537.5375**

fax order toll-free (USA & Canada) | phone order toll-free (Mexico) | tech support toll-free (USA & Canada) | e-mail
1.888.288.6900 | **001.888.304.1307** | **1.866.467.9001** | sales@imscompany.com

