

IMS 1½ HP Belt Drive Double Drum Tumbler

Mixes two drums quickly and effectively




- Heavy ship channel and solid steel plate frame with continuous welds for maximum strength
- Heat treated main shaft
- 2" wide nylon quick release safety belt
- High ratio gear reducer for ample torque
- Completely enclosed drives for safety
- Ample access to all components for easy maintenance
- Drawing included for protective enclosure

High Torque Drive Belt:

- Provides smooth power transmission
- Needs no lubrication
- Requires virtually no adjustment
- Absorbs start-up torques and stopping impacts
- Reduces wear and tear on tumbler parts



ONLY FROM IMS



Belt guard removed for illustration only

Purchasers also order:

- Remote Control Panel, page 679
- Drums for mixing and storage, pages 680-681
- Drum Cart, page 683

Note: Stainless steel drums (shown) sold separately. See page 680

Specifications and Prices

Load Limit: 280 lbs. per holder(including drum)
Motor: 1.5 HP (TEFC) 1725 rpm, 208/240/480/60/3
Amperage: 4.8 (240 volts), 2.4 (480 volts)

Tumbling Speed: 18 rpm
Drive Belt: heavy torque drive
Operating Space: 110" x 59" (with drums)
Crated Weight: 916 lbs.

Drum Sizes and Holders	30 Gallon Holder	55 Gallon Holder
Maximum drum height	34"	37"
Minimum drum height	30"	33"
Maximum drum diameter	22"	25"
Minimum drum diameter	20"	21.5"

Item #	Description	Prices
111871	1.5 HP Belt Drive Double Tumbler only (no holders) and four lag bolts	\$3,490
111869	Tumbler with two 30-gallon drum holders (#107873) and four lag bolts	5,100
111879	Tumbler with two 55 gallon drum holders (#107857) and four lag bolts	5,100



= Highest Quality & Value Products



= Industry Standard Quality Products



= Value-Priced Supplies



www.imscompany.com | phone order toll-free (USA & Canada) **1.800.537.5375**

fax order toll-free (USA & Canada)

phone order toll-free (Mexico)

tech support toll-free (USA & Canada)

e-mail

1.888.288.6900

001.888.304.1307

1.866.467.9001

sales@imscompany.com

