



Pro-17 Inhibited Propylene Glycol

Non-toxic heat transfer fluid with maximum protection against acidity and corrosion

- ★ Non-toxic to people, animals and the environment
- ★ Flushable to sewer and septic systems
- ★ High-end corrosion inhibitor package to protect your equipment

Contains undiluted propylene glycol for environmental safety, plus our industry-leading inhibitor package to prevent corrosion - the same inhibitor as our EG-17.

AVOID THE TOXICITY OF ETHYLENE GLYCOL

AVOID THE CORROSIVE ACID FORMATION OF STRAIGHT PROPYLENE GLYCOL

SPECIFICATIONS

(Undiluted Pro-17)

- Color:** Pink
- pH:** 8.5 - 10.0
- Flash Point:** 215° F
- Specific Gravity:** 1.13 ± 0.01
- BP @ 760 mm Hg:** 310° F (154° C)
- VP mm Hg @ 68° F:** <1

NOTE: In most cases, propylene glycol can be substituted for ethylene glycol. It is thicker than ethylene glycol and a little harder to pump; so the pump might not be able to deliver quite as much pressure.



Usage:

- Use at least 30% Propylene Glycol for corrosion resistance.
- Use the lowest concentration (above 30%) that allows you to reach the required temperature (for maximum heat transfer). Use the chart at bottom/left as a guide.
- Avoid using more than 50% if possible — heat transfer is very low above that level.

Pro-17 Propylene Glycol Heat Transfer Fluid

Temperature and Concentration Chart

Temperature ranges versus Pro-17 concentration

° F	% Pro-17	% Water
9° to 216°	30	70
2° to 217°	35	65
-6° to 220°	40	60
-28° to 223°	50	50

Item No.	Quantity	Price (each)
132562 (5 gallon pails)	1	\$ 133.40
	2-5	126.73
	6+	120.06
132561 (55 gallon drum)	1	1,250.05
	2+	1212.55



Mold Chiller Flushing Fluid

Removes scale and deposits from chiller components

- Decreases cycle times – improves flow and heat transfer in water and glycol systems
- Use in 1% to 2% concentration in water

Item No.	Price
138216 (5 gallon pails)	\$237.20



www.imscompany.com | phone order toll-free (USA & Canada) **1.800.537.5375**

fax order toll-free (USA & Canada) | phone order toll-free (Mexico) | tech support toll-free (USA & Canada) | e-mail
1.888.288.6900 | **001.888.304.1307** | **1.866.467.9001** | sales@imscompany.com

