

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: SDS Number: Product Code: Revision Date: Version: Product Type:	AP Mold Cleaner IMS 06-508-12 118313 11/16/2022 2 Aerosol Mold Cleaner
Supplier Details:	IMS Company 10373 Stafford Rd. Chagrin Falls, OH 44023-5296
Phone:	1-440-543-1615
Emergency:	Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1 Physical, Gases Under Pressure, Liquefied Gas Health, Aspiration hazard, 1 Health, Skin corrosion/irritation, 2 Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

- H222 Extremely flammable aerosol
- H280 Contains gas under pressure; may explode if heated
- H304 May be fatal if swallowed and enters airways
- H315 Causes skin irritation
- H336 May cause drowsiness or dizziness

GHS Precautionary Statements:

- P210 Keep away from heat/sparks/open flames/hot surfaces.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
- P331 Do NOT induce vomiting.
- P405 Store locked up.
- P410 + P403 Protect from sunlight. Store in a well-ventilated place.
- P412 Do not expose to temperatures exceeding 50 °C/ 122 °F.
- P501 Dispose of contents/container in accordance with local/ regional regulations

COMPOSITION/INFORMATION OF INGREDIENTS

	Chemica	l Ingredients:
CAS#	%	Chemical Name:
124-38-9 64742-48-9	.1-10% 85-99%	Carbon dioxide (propellant) Synthetic Isoparaffinic Hydrocarbon

4 FIRST AID MEASURES

Inhalation: Skin Contact:	Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician. Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Eye Contact:	Flush with warm water for 15 minutes. Seek medical attention.
Ingestion:	Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

FIRE FIGHTING MEASURES

Flash Point:

5

3

Flash point of liquid portion 104°F

LEL:	Lower: 0.7 % (VOL.) Gas in air (liquid portion)
UEL:	Upper: 5.6 % (VOL.) Gas in air (liquid portion)

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials. Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite. Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.



ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7

HANDLING AND STORAGE

Handling Precautions:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated

leather clothing.

	Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate
Storage Requirements:	Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials
8 EX	KPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls:	General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.
Personal Protective Equipment:	Protective Equipment: Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.
	Engineering Controls: General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.
	Respiratory Protection: Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required Other Suggested Equipment: Eye wash station and emergency showers should be available. Spill containment equipment should be available.
	Discretion Advised: We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.
Carbon dioxide (propellant)	cas#:(124-38-9) [.1-10%]
Components with workplace	control parameters
TWA 5,000 ppm Asphyxia	USA. ACGIH Threshold Limit Values (TLV)
STEL 30,000 ppm Asphyxia	USA. ACGIH Threshold Limit Values (TLV)
TWA 10,000 ppm 18,000 mg/m3 Exposures under 10,000 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 n to be cited as de minimus.
STEL 30,000 ppm 54,000 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
TWA 5,000 ppm 9,000 mg/m3 The value in mg/m3 is approx	USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants kimate.
TWA 5,000 ppm 9,000 mg/m3 Normal constituent of air (abc	USA. NIOSH Recommended Exposure Limits out 300 ppm).
ST 30.000 ppm	USA NIOSH Pacammandad Expansional imite

ST 30,000 ppm USA. NIOSH Recommended Exposure Limits

54,000 mg/m3 Normal constituent of air (about 300 ppm).

9 PHYSICAL AND CHEMICAL PROPERTIES Appearance: Clear Aerosol Viscosity: NA Odor: Negligible **Boiling Point:** Solubility: Negligible NE Flammability: **Extremely Flammable** Freezing/Melting Pt.: NE **Partition Coefficient:** NE Flash Point: Flash point of liquid 104°F Vapor Pressure: >30 psi Vapor Density: >1 Air = 1 pH: NA **Bulk Density:** NE Evap. Rate: Ether = 1 Slower STABILITY AND REACTIVITY 10

Chemical Stability:StableConditions to Avoid:Heat, spark, and open flame.Materials to Avoid:Strong Oxidizing Agents.Hazardous Decomposition:Combustion will produce Carbon Monoxide, Carbon Dioxide, and hydrocarbons.Hazardous Polymerization:Will not occur.

11

TOXICOLOGICAL INFORMATION

Carbon dioxide (propellant) cas#:(124-38-9) [.1-10%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50 Dermal LD50 Other information on acute toxicity

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May cause severe frostbite. May be harmful if absorbed through skin. May cause skin

Eyes May cause eye irritation. Aggravated Acts as a simple asphyxiant by displacing air. , Medical Condition

Signs and Symptoms of Exposure: Nausea, Dizziness, Headache, Low to medium concentrations of carbon dioxide can:, affect regulation of blood circulation, affect the acidity of body fluids, respiratory difficulties, At high concentrations:, Breathing difficulties, Increased pulse rate, change in body acidity, Very high concentrations can cause:, Unconsciousness, death

Synergistic effects: no data available

Additional Information:

RTECS: FF6400000

12	ECOLOGICAL INFORMATION	
Carbon dioxide (propellant) cas#:(124-38-9) [.1-10%]		
Information on ecological effects		
Toxicity: no data available		
Persistence and degradability: no data available		
Bioaccumulative potential: no data available		
Aobility in soil: no data available		
PBT and vPvB assessment: no data available		

Other adverse effects: no data available

DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14

13

TRANSPORT INFORMATION

Aerosols (limited quantity), Class 2.1, ERG 126

AIR (IATA) Aerosols (limited quantity), Class 2.1, ERG 126, UN No. 1950

Vessel Aerosol (Limited Quantity), Class 2.1, UN No 1950

15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[.1-10%] Carbon dioxide (propellant) (124-38-9) MASS, OSHAWAC, PA, TSCA, TXAIR

[85-99%] Synthetic Isoparaffinic Hydrocarbon (64742-48-9) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

NFPA: Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/16/2022